



Umbilical Applicators

Optional Extras:

- Smart Spread Flow meter compatible with 10' Tablet or ISOBUS
- Single splashplate
- Wireless rear camera
- LS load-sensing hydraulic system
- Touch screen operating system
- Can be supplied with Skate Board for JD Harvest Lab

Mastek Vertical Dribble Bar / Drag Hose

The Mastek Vertical Dribble Bar/ Drag Hose is designed to allow precise application of slurry to grassland and crops with the minimum of crop disturbance. Our machines are specifically designed for Umbilical (Drag-Hose systems) . Vertical Dribble Bar can operate with or without its 800m/1200m quick release reel. The 8m systems have spring-loaded hinge arms. The 10m and 12m systems have a uniquely designed strong 180° hinging system, which gives it minimum height in transport.



Spreading **Sustainability**
REDUCING EMISSIONS



www.mastek.ie

Mastek Ltd Ireland
Cootehill Business Park
Cootehill
Co. Cavan
H16 DX45, Ireland
Tel: +353 (0) 49 555 5953
Email: enquiries@mastek.ie

Mastek Ltd UK
Alderton Farm
Harmer Hill, Shrewsbury
Shropshire
SY4 3EL United Kingdom
Tel: + 01939 220079
Email: uksales@mastek.ie

Product Specifications

Working Width	Transport Height	Closed Width	No. of Outlets	Weight	Depth
8.2m	3.7m	2.35m	28	1080kg	1.2m
9m	2.955m	2.35m	40	1120kg	1.2m
10m	2.955m	2.35m	40	1200kg	1.2m
12m	3.45m	2.35m	48	1340kg	1.2m

Mastek Super Cut Macerator

All Mastek products are fitted with Mastek Super Cut Macerator. It will macerate and distribute evenly with our 48 outlet macerator, even on the most hilly conditions. This is achieved by our air breather one-way valves, which are uniquely placed above every outlet pipe. This valve sucks in the air as the serrated knife-cutters pass by each outlet, allowing the slurry to flow without resistance or air-locking. This system gives a $\pm 98\%$ accurate distribution. Each sideplate screen can be supplied with various hole sizes to increase and decrease the slurry flow.

Features:

- Capable of cutting high-fibre slurry
- Even outlet distribution
- 2.5m of long-life combined cutter blades edge
- Individual air breathers for each outlet pipe
- Available in 40mm & 45mm tube with 28,30, 40 or 48 outlets
- Low maintenance
- Easy access door
- Hydraulic motor protection

